



RATCHETING HEAD MICROMETER TORQUE WRENCHES

MEETS ASME STANDARD

- › Calibrated to +/- 4% clockwise direction and +/- 6% counter clockwise direction at 20% to 100% of full scale.
- › Calibration is accomplished by manually loading the torque wrenches.
- › Manufactured to meet standard industrial torque applications, general industry, heavy equipment, and maintenance.
- › Locking pin Detent to retain Socket during use.



FT-LBS

Product #	Drive Size (in)	Torque Range (ft-lbs)	Increments (ft-lbs)	Head Width (in)	Head Depth (in)	Overall Length (in)	Weight (lbs)	Storage Case	Repair Kit
J6012C-TT	3/8	20-100	0.5	1-7/16	1-1/64	17	3.30	J6006PBF	J6006RK-TT
J6014C-TT	1/2	50-250	1	1-7/8	1-13/32	27-1/8	5.90	J6014PBF	J6014RK-TT

NOTE: For use with Elastic Bungee or Web Lanyard only.

 ASME B107.14M

NM

Product #	Drive Size (in)	Torque Range (Nm)	Increments (Nm)	Head Width (in)	Head Depth (in)	Overall Length (in)	Weight (lbs)	Storage Case	Repair Kit
J6006NMC-TT	3/8	16-80	0.5	1-7/16	1-1/64	15-1/2	3.00	J6006PBF	J6006RK-TT
J6016NMC-TT	1/2	40-200	1	1-7/8	1-13/32	21-1/2	5.00	J6014PBF	J6014RK-TT

NOTE: For use with Elastic Bungee or Web Lanyard only.

 ASME B107.14M

Ty-Flot products in blue are covered under a Limited Warranty provided by Ty-Flot, Inc.



WARNING: WORK SAFELY WITH TOOLS. WEAR SAFETY GOGGLES.

+1.800.800.TOOL • Fax: +1.800.828.7809 • www.protoindustrial.com